# SAFETY DATA SHEET.

Issuing date 11-Nov-2015 Revision Date 17-Dec-2019 Version 4.03

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name LAMI-LUBE III

Recommended use of the chemical

and restrictions on use

Product code F03133

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use Non-Silicone Multi-Purpose Dry Lubricant with PTFE for Woodworking Equipment and

Hand Tools.

Uses advised against No information available

Manufactured For: Manufacturer

Lami-Lube Products American Jetway Corporation

9435 Old Airport Highway 34136 Myrtle Street
Monclova, OH 43542-9557 Wayne, MI 48184-0126
Phone: (419) 866-1845 Phone: (734) 721-5930

Emergency telephone number

Chemical Emergency Phone CHE

Number

CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

F03133 - LAMI-LUBE III Revision Date 17-Dec-2019

### 2. HAZARDS IDENTIFICATION

#### Classification

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### Hazard Statements

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation. May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Hazy Physical state Aerosol Odor Solvent

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling.

Wear protective gloves, eye protection, face protection.

Avoid breathing fumes, gas, mist, vapors, spray.

Use only outdoors or in a well-ventilated area.

Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

#### **Precautionary Statements - Response**

Specific treatment (see first aid on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice, attention

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice, attention.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor, physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.

Do NOT induce vomiting.

#### **Precautionary Statements - Storage**

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents, container to an approved waste disposal plant.

#### Hazards not otherwise classified (HNOC)

None

#### Other information

0.000005% of the mixture consists of ingredient(s) of unknown toxicity.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	45-55
HEPTANE	142-82-5	20-30
ACETONE	67-64-1	15-25
POLYTETRAFLUOROETHYLENE	9002-84-0	1-10
PETROLEUM DISTILLATES	8052-41-3	<1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

**General advice** Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

Skin contact Wash off with soap and plenty of water. Remove and wash contaminated clothing before

re-use. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never

give anything by mouth to an unconscious person. Risk of product entering the lungs on

vomiting after ingestion.

**Protection of First-aiders** Remove all sources of ignition.

### Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and serious eye irritation. May cause respiratory irritation. May cause

drowsiness or dizziness. May be fatal if swallowed and enters airways.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources

of ignition - No smoking.

#### Specific hazards arising from the chemical

Extremely Flammable / Flammable. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Hazardous Combustion Products

Acrid smoke/fumes. Carbon oxides, Hydrocarbons, Fumes. Sulfur oxides.

·····

**Explosion Data** 

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal

regulations. Do not flush into surface water or sanitary sewer system. Do not allow material

to contaminate ground water system. Should not be released into the environment.

#### Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away

from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

#### Conditions for safe storage, including any incompatibilities

**Technical measures/Storage** 

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m³
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m³ 15 min TWA: 85 ppm TWA: 350 mg/m³
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
PETROLEUM DISTILLATES 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

**Engineering Measures**Ventilation systems. Use adequate ventilation to keep the exposure levels below the

occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields. Tightly fitting safety goggles.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

Physical state Aerosol

Appearance Hazy Odor Solvent

Color Hazy Odor Threshold

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

pH No information available Melting/freezing point No information available

Boiling point/boiling range

Flash Point -97 °C / -143 °F Based on propellant

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity 0.651

Water solubility No information available

Partition coefficient: n-octanol/water

Autoignition temperature
Decomposition temperature

No information available

Viscosity
Explosive properties

No information available

Other information

**VOC Content(%)** 77.55

### 10. STABILITY AND REACTIVITY

Not applicable

#### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

### **Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

#### **Hazardous Decomposition Products**

Carbon oxides, Hydrocarbons, Fumes.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** May cause respiratory irritation, May cause drowsiness or dizziness.

**Eye contact** Causes serious eye irritation.

**Skin contact** Causes skin irritation.

**Ingestion** May be fatal if swallowed and enters airways.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEPTANE	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> (Rat) 4 h
142-82-5			
ACETONE	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
67-64-1			

#### Information on toxicological effects

**Symptoms** Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause

respiratory irritation. May be fatal if swallowed and enters airways.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationIrritating to skin.Eye damage/irritationIrritating to eyes.SensitizationNot a known sensitizer.Germ cell mutagenicityNot a germ cell mutagen.

**Carcinogenicity**The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
POLYTETRAFLUOROETHY	-	Group 3	-	-
LENE				
9002-84-0				

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

This product does not contain a chemical(s) which is a known or suspected reproductive

hazard.

Specific target organ systemic toxicity (single exposure)

Specific target organ systemic

toxicity (repeated exposure)

May cause respiratory irritation. May cause drowsiness or dizziness.

No known effect based on information supplied.

Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

Target Organ Effects Skin, Eyes, Respiratory System, and Central Nervous System.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

**Aspiration hazard** May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.000005% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5715 mg/kg
ATEmix (dermal) 7152 mg/kg
ATEmix (inhalation-gas) 198334 mg/l
ATEmix (inhalation-dust/mist) 245.6 mg/l
ATEmix (inhalation-vapor) 271.8 mg/l

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				
HEPTANE	=	375.0 mg/L LC50 Cichlid fish	-	-
142-82-5		96h		
ACETONE	-	4.74 - 6.33 mL/L LC50	-	10294 - 17704 mg/L EC50
67-64-1		Oncorhynchus mykiss 96h		Daphnia magna 48h Static
		6210 - 8120 mg/L LC50		12600 - 12700 mg/L EC50
		Pimephales promelas 96h		Daphnia magna 48h
		static 8300 mg/L LC50		
		Lepomis macrochirus 96h		

### Persistence and degradability

.

#### **Bioaccumulation**

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	
HEPTANE	4.66
142-82-5	
ACETONE	-0.24
67-64-1	

Other adverse effects No information available

### 13. DISPOSAL CONSIDERATIONS

#### **Waste treatment**

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with local regulations. Dispose of in accordance with federal, state, and local

regulations.

**Contaminated packaging**Do not re-use empty containers. Empty containers should be taken to an approved waste

handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even

after use.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD.QTY

F03133 - LAMI-LUBE III Revision Date 17-Dec-2019

### 15. REGULATORY INFORMATION

SCHEDULE B CODE: 3403.99.0000.

#### **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Х	Х	Х	Х	Х
HEPTANE	Х	Х	X	X	X	X	Х	X
ACETONE	Х	Х	X	X	X	X	X	X
POLYTETRAFLUORO ETHYLENE	Х	Х	Not listed	Х	Х	Х	Х	Х
PETROLEUM DISTILLATES	Х	Х	X	Х	Х	Х	Х	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **U.S. Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

### SARA 311/312 Hazard Categories

Acute Health Hazard

Chronic Health Star Hazard

Fire Hazard

Sudden Release of Pressure Hazard

Reactive Hazard

Yes

Yes

Yes

No

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

### **U.S. State Regulations**

### California Proposition 65

This product does not contain any Proposition 65 chemicals.

F03133 - LAMI-LUBE III Revision Date 17-Dec-2019

\_\_\_\_\_

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEPTANE	X	X	X
142-82-5			
ACETONE	X	X	X
67-64-1			
POLYTETRAFLUOROETHYLENE			X
9002-84-0			
PETROLEUM DISTILLATES	X	X	X
8052-41-3			

EPA Pesticide Registration Number Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

### **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

<u>HMIS</u> Health Hazard 2\* Flammability 4 Physical Hazard 1 Personal protection B Chronic Hazard Star Legend Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system

damage

Prepared By American Jetway Corporation

34136 Myrtle Street Wayne, MI 48184-0126

Issuing date 11-Nov-2015 Revision Date 17-Dec-2019

**Revision Note** 

(M)SDS sections updated 3 15 1

#### **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**